



AGM
GLOBAL
VISION

З питань придбання тепловізора в Україні звертайтеся на сайт <https://pipl.ua/>, за телефоном +38 (073) 600-500-2 або електронною адресою order@pipl.ua

TAIPAN TM10-256

THERMAL IMAGING MONOCULAR



The Taipan TM10-256 handheld observational thermal monocular is equipped with a 256x192 infrared detector and a 720x540 LCOS display. It supports functions of observation, highest temperature target tracking, distance measurement, Wi-Fi hotspot, and so on. The high-sensitivity built-in thermal detector provides you with clear view even in total darkness. The monocular is mainly applied to scenarios such as patrolling, law enforcement, searching and rescuing, drug enforcement, anti-smuggling, criminal seizing, hiking, travel, and hunting, etc.

- 256x192 resolution, 12 μm , high sensitivity detector
- Adaptive AGC, DDE, 3D DNR
- 720 x 540 LCOS display
- Built-in rechargeable Lithium battery
- Up to 8 hours continuous running (with Wi-Fi hotspot function off)
- "Auto Power Off" and "Sleep" modes
- Wi-Fi hotspot
- Type-C interface
- Limited 3-year warranty

FUNCTIONS

Distance Measurement:

The device realizes distance measurement function after marking the top and bottom of target, and input the target height.

Hot Spot Mark:

The device detects and marks the hot spot of highest temperature.

Mode Switch:

Device supports pallet switch and distance measurement.

Storage:

Built-in memory module supports video recording/snapshot capturing.

Digital Zoom:

Device supports 1x, 2x, 4x, and 8x digital zoom.

Wi-Fi Hotspot:

Device can capture snapshots, record videos, and set parameters via APP after being connected to your phone.



SPECIFICATIONS

Item	Taipan TM10-256
Detector Type	Vanadium Oxide Uncooled Focal Plane Arrays
Resolution	256x192
Pixel Interval	12 μ m
Refresh Rate	25 Hz
Response Waveband	8 μ m to 14 μ m
NETD	Less than 35 mk (@25°C), F#=1.0
Detection Range	458 m
Lens (Focal Length)	10 mm
Aperture	F1.0
Field of View	18.00° x 13.55° (H x V)
Magnification	1x to 8x
Digital Zoom	1x, 2x, 4x, 8x
Monitor	720x540, 0.2 inch, LCOS
FFC (Flat Field Correction)	Auto, Manual, External Correction
Palettes	Black Hot, White Hot, Red Hot, Fusion
Highest Temperature Spot Tracking	Yes
Wi-Fi Hotspot	Yes
Standby Mode	Yes
Storage	Built-in memory module (8 GB)
Record Video	On-board video recording
Capture Snapshot	Yes
CVBS Output	Yes (via USB)
Multi Language menu	Yes
Battery Type	Built-in rechargeable Lithium battery
Battery Operating Time	Up to 8 hours continuous running (with Wi-Fi hotspot function off)
Battery Capacity Display	Yes
Power	5 VDC/2 A, 1.5 W
Interface	USB Type-C
Working Temperature	-20°C to 55°C (-4°F to 131°F)
Protection Level	IP67
Drop Test Height	1.5 m (4.9 feet)
Dimension	158 x 61 x 57 mm (6.23 x 2.4 x 2.2 in)
Weight	260 g (0.57 lb)

Specifications are subject to change without notice.



З питань придбання тепловізора в Україні звертайтеся на сайт <https://pipl.ua/>, за телефоном +38 (073) 600-500-2 або електронною адресою order@pipl.ua

MAIN OFFICE | 173 West Main Street | PO Box 962 | Springerville, AZ 85938, USA
Tel. +1.928.333.4300 | info@agmglobalvision.com | www.agmglobalvision.com

EUROPEAN OFFICE | Andrey Lyapchev #7 | Sofia, P.C. 1756 | Bulgaria
Tel. +35.988.412.5573 | info@agmglobalvision.eu | www.agmglobalvision.eu

www.agmglobalvision.com